



TR 3.60 H

PORTABLE POWER

Water Pumps Range INTENS AQUALINE

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Resistant pump-barrel
- Automatic priming
- Easy acces to the turbine
- Offeres accessories

The AQUALINETM INTENS TR 2.36 H and TR 3.60 H models have a very high quality pump body and are designed for treating dirty water intensively and reliably. The front cover can be removed for quick cleaning, which is a considerable help for professionals.

Range INTENS AQUALINE

Designed for water with low solid content.



TR 3.60 H

WATER PUMP SPECIFICATIONS

Range	INTENS AQUALINE
Type liquid	Heavily sedimented water pump
Suction diameter [mm]	80
Backflow diameter (mm)	80
Outflow maximum (L/min)	900
Outflow maximum (m3/h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	3.10
75% cons. (l/h) *	0.90
75% Autonomy (h) *	3.40
Sound power level guaranteed LwA dB(A)	105
Acoustic pressure level @1m in dB(A)	91
Acoustic pressure level @7m in dB(A)	76

ENGINE SPECIFICATIONS

Engine model	HONDA
Engine ref.	GX160
Distribution	O.H.V.
Start	Starter
Oil Guard	Oui
Capacity (cm3)	163
Oil capacity (L)	0.60

DIMENSIONS AND WEIGHT

Length (cm)	50.50
Width (cm)	39.80
Height (cm)	46.60
Dry Weight (kgs)	29

PACKAGING

Packaging type	Box
Length (cm)	51.50
Width (cm)	42
Height (cm)	48
Weight (kg)	34.50
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	157
weight of the packaged Pallet (kg)	424



ACCESSORIES SUPPLIED



Inlet filter
Screw-on connectors



Circlips
User and maintenance manual

OPTIONS



RBH1	Cans of oil	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
RBH0-5	Cans of oil	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).
RHO	Protection cover	Cover for SDMO 's generating sets, welding sets and water pumps
R12	Piping kit 3	Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.
R14	Rapid connectors 3	Rapid connections kit for 3 water pumps.